



Rotary pump-PP-FKM

SRL 1050-10 I/min

Item number: 13 065

EAN: 4103810130656

Technical data

Delivery rate (I/rotation): 0,18
Delivery rate at 60 rotations/min (I/min): approx. 10

Pumping media: thin liquids, such as windshield washer, diesel,

water, AdBlue®

Media resistance: see resistance table
Usage: container for 60 / 200 / 220 I

Application: for filling measuring vessels, storage cans and

canisters

Length of suction tube (mm): 1050
Barrel screw coupling: G 2" male

Materials of parts in contact with liquid

Pump housing: PP

Seals: FKM (Viton®)

Discharge: PF

Dimensions LxWxH (mm): 250 x 220 x 1325

Weight (kg): 1,12

Specification

- With suction filter
- Adjustable height through barrel screw coupling
- Packed in carton box
- Possible accessories: M 56 x 4 male (13 080 390), Mauser 2" male (13 083)

Special notes

- Information: In the case of the formation of crystals, clean the pump with warm water until all crystals are dissolved
- According to consistency table
- Suitable for thin liquids, such as windshield washer, diesel, water, AdBlue®

Packaging

Packaging: Carton

Dimensions LxWxH (mm): 360 x 180 x 165

Weight including package (kg): 1,66
Packing unit: 1,0