

Hose reel for oil

O-WB-120 bar-DN 12-10 m

-
(
L
(

Item number: EAN: Discount group: 29 142 4103810291425 D

Technical data

Length of discharge hose (m): Connection discharge hose: Length of connecting hose (m): Connection to connecting hose: Inner diameter of hose (DN): Operating pressure max. (bar): Lacquering Arm: Supporting plate: Encasing: Dimensions LxWxH (mm): Weight (kg): 10 G 1/2" male/female 1 G 1/2" female/female 12 120

window grey, satin, RAL 7040 window grey, satin, RAL 7040 blue, Pantone 294 C 472 x 152 x 498 16,6

Specification

- Open, for wall/floor mounting
- With hose stop

Special notes

- Pressol hose reels are exceedingly robust and are notable for their compact design
- All metal parts are phosphatized, undercoated and painted
- The high quality surface treatment of all steel parts ensures high corrosion resistance
- Axis (Ø 40 mm) of die cast parts. Dimensions selected by our engineers ensure almost unlimited life range
- The material combination axis / bearing and the spring unit are maintenance-free
- Easy assembly because the weight of the hose reel does not need to be supported while mounting
- All swivel joints are ball bearing based
- High pressure in the supply system does not influence the power needed to rotate the drum
- The hose can be engaged by rotating 1/4 turn

Packaging

 Dimensions LxWxH (mm):
 540 x 580 x 160

 Weight (kg):
 18,50

 Packing unit:
 1,0